

Page 1 of 9 -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

PRODUCT AND COMPANY INFORMATION

Product Name: Gulf Select Heavy Duty DOT 3 Brake Fluid

Revision Date: 12/18/2015 SDS Number: GS710

<u>Common Name:</u> Automotive brake fluid

<u>CAS Number:</u> Blend <u>Product Code:</u> GS710

Synonyms: Automotive brake fluid

Company Identification:

Supplier:

NU-TIER BRANDS, INC. 8282 S. Memorial Drive, Suite 302 Tulsa, OK 74133 www.gulflubricants.net

Under license from Gulf Oil LP

For Product Information: 1-800-566-4853

For Emergencies: 1-800-424-9300 (CHEMTREC)

HAZARDS IDENTIFICATION



Signal Word: DANGER

Hazard Classes/Categories:

Acute toxicity, Oral category 4. Serious eye damage, Category 1.



Page 2 of 9 -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

Hazard Statement(s):

H302: Harmful if swallowed.

H318: Causes serious eye damage.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P264: Wash hands, face, and exposed skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue

rinsing.

P310: Immediately call a POISON CENTER/doctor.

P301+310: IF SWALLOWED: Immediately call a POISON

CENTER/doctor. P330: Rinse mouth.

P501: Dispose of contents/container in accordance with

local/regional/national/international regulation.

Other Hazard Statement(s):

-NFPA Ratings:

Health = 0

Fire = 0

Reactivity = 0

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Triethylene glycol, monobutyl ether	143-22-6	15-30
Diethylene glycol	111-46-6	15-25
Diethylene glycol monobutyl ether	112-34-5	10-20
Ethanol, 2-(2-propoxyethoxy)	6881-94-3	5-10

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Page 3 of 9 -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

4 FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

Get medical attention immediately if symptoms occur.

Skin Contact:

Wash off immediately with soap and plenty of water. Get medical

attention immediately if symptoms occur.

Eye Contact:

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a

physician or Poison Control Center immediately.

Ingestion:

Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Drink plenty of water. Call a POISON CENTER or

doctor/physician if exposed or you feel unwell.

Symptoms and Effects, both acute and delayed:

Burning. Red eyes Tearing

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.

FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.



Page 4 of 9 -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid eye contact. Avoid repeated or prolonged

skin contact.

Personal protective equipment must be worn. Avoid contact with skin, eyes or clothing.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labeled containers.

Environmental Precautions:

Do not allow product to reach sewage system or

any water course.

Inform respective authorities in case of seepage

into water course or sewage system.

Cleanup Procedures:

Absorb with liquid-binding material (sand,

diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

HANDLING AND STORAGE

Handling Precautions:

Wear personal protective equipment. Do not get in

eyes



Page **5** of **9** -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

Storage Requirements:

Keep containers tightly closed in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Engineering Controls:

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Use safety glasses and gloves.

9 PHYSICAL AND CHEMICAL PROPERTIES

Color: Amber
Physical State: Liquid
Odor: Etheric

Odor Threshold: Data not available

pH: 10.5

Melting Point: Data not available

Boiling Point: 205° C

Boiling Range: Data not available

Flash Point: 203° C

Evaporation Rate:

Flammability:

Data not available

Plammability Limits:

Data not available

Data not available

Data not available

Vapor Pressure:

Data not available

Vapor Density:

Data not available

Relative Density: 1.06

Solubilities: Fully miscible with water

Partition Coefficient:

Auto-Ignition Temperature:

Data not available

Decomposition Temperature:

Data not available

Data not available

Viscosity: <1500 cSt



Page **6** of **9** -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

10	STABILITY AND REACTIVITY	
Stability:		Stable under normal conditions.
Reactivity:		Not reactive under normal conditions.
Conditions to A	void:	No further relevant information available.
Hazardous Reac	ctions:	No known hazardous reactions.
Incompatible M	<u>aterials:</u>	Strong oxidizers.
Decomposition	Products:	Oxides of carbon.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Inhalation, skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

- On the skin: May cause irritation.

- On the eye: Causes serious eye damage.

Inhalation: May cause respiratory tract irritation.Ingestion: Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea.

Measures of Toxicity:

Oral LD50: 1667 mg/kg (ATE)

Dermal LD50: 4606 mg/kg (ATE)

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.



Page **7** of **9** -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Do not allow product to reach ground water, water course or sewage system.

Ecological Effects:

-Triethylene glycol, monobutyl ether:

EC50 72 h: > 500 mg/L (Desmodesmus subspicatus) LC50 96 h: 2200-4600 mg/L

static (Leuciscus idus) LC50 96 h: = 2400 mg/L (Pimephales promelas) LC50 96 h: = 2400 mg/L static (Pimephales promelas) EC50 48 h: > 500 mg/L

EC50 48 h: > 500 mg/L (Daphnia magna)

-Diethylene glycol:

LC50 96 h: = 75200 mg/L flow-through (Pimephales promelas)
EC50 = 29228 mg/L 15 min EC50 48 h: = 84000 mg/L (Daphnia magna)

-Diethylene glycol monobutyl ether:

EC50 96 h: > 100 mg/L (Desmodesmus subspicatus) LC50 96 h: = 1300 mg/L static (Lepomis macrochirus) EC50 24 h: = 2850 mg/L (Daphnia magna) EC50 48 h: > 100 mg/L (Daphnia magna)



Page 8 of 9 -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

-Tetraethylene glycol:

EC50 96 h: > 1000 mg/L (Pseudokirchneriella subcapitata) LC50 96 h: > 1000 mg/L static (Oncorhynchus mykiss)

EC50 > 100 mg/L 6 h EC50 48 h: > 1000 mg/L

(Daphnia magna)

-Triethylene glycol:

LC50 96 h: 56200-63700 mg/L flow-through (Pimephales promelas)
LC50 96 h: = 10000 mg/L static (Lepomis macrochirus)
LC50 96 h: = 61000 mg/L flow-through (Lepomis macrochirus)

EC50 = 850 mg/L 5 min EC50 48 h: = 42426 mg/L

(Daphnia magna

13 DISPOSAL CONSIDERATIONS

Special Precautions:

<u>Disposal Methods:</u>

Dispose of waste material in accordance with all

local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Do not dispose of with household garbage.

Do not flush to surface waters or drains.



Page 9 of 9 -

Gulf Select Heavy Duty DOT 3 Brake Fluid

SDS Number: GS710

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 12/18/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. The supplier assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the supplier.